

PASSI RAPIDI

FRAMO SHOWER





PR01QCR

OTTONE CROMO
CHROMED BRASS

Flussometro ad incasso normale da 3/4", con piastra e leva quadrata, in ottone

3/4" built-in brass flush valve with square cover plate and lever



PR02QCR

OTTONE CROMO
CHROMED BRASS

Flussometro ad incasso normale da 1", con piastra e leva quadrata, in ottone

1" built-in brass flush valve with square cover plate and lever



PR01TCR

OTTONE CROMO
CHROMED BRASS

Flussometro ad incasso normale da 3/4", con piastra e leva minimale, in ottone

3/4" built-in brass flush valve with minimal cover plate and lever



PR02TCR

OTTONE CROMO
CHROMED BRASS

Flussometro ad incasso normale da 1", con piastra e leva minimale, in ottone

1" built-in brass flush valve with minimal cover plate and lever

PR01E



PR01ECR

OTTONE CROMO
CHROMED BRASS

Flussometro ad incasso normale da 3/4", con piastra e leva standard, in ottone

3/4" built-in brass flush valve with standard cover plate and lever

PR02E



PR02ECR

OTTONE CROMO
CHROMED BRASS

Flussometro ad incasso normale da 1", con piastra e leva standard, in ottone

1" built-in brass flush valve with standard cover plate and lever



PR03ECR

OTTONE CROMO
CHROMED BRASS

Flussometro esterno normale da 3/4", con piastra e leva standard, in ottone

3/4" brass external flush valve with standard cover plate and lever



PR04ECR

OTTONE CROMO
CHROMED BRASS

Flussometro esterno normale da 1", con piastra e leva standard, in ottone

1" brass external flush valve with standard cover plate and lever



PR01TEMPCR

OTTONE CROMO
CHROMED BRASS

Flussometro temporizzato ad incasso da 3/4", studiato contro colpo d'ariete. Pressione ottimale da 0,5 a 3 atm. Tempo apertura 3/5"

3/4" self closing built-in flowmeter, expressly studied against water hammer advisable pressure from 0,5 to 3 atm. Standard opening time 3/5"

PRO2TEMP



PRO2TEMPCR

OTTONE CROMO
CHROMED BRASS

Flussometro temporizzato ad incasso da 1", studiato contro colpo d'ariete. Pressione ottimale da 0,5 a 3 atm. Tempo apertura 3/5"

1" self closing built-in flowmeter, expressly studied against water hammer. Advisable pressure from 0,5 to 3 atm. Standard opening time 3/5"

PRO3TEMP



PRO3TEMPCR

OTTONE CROMO
CHROMED BRASS

Flussometro temporizzato esterno da 3/4". Pressione ottimale da 0,5 a 3 atm. Tempo apertura 3/5"

3/4" brass external flush valve flowmeter. Advisable pressure from 0,5 to 3 atm. Standard opening time 3/5"

PRO4TEMP



PRO4TEMPCR

OTTONE CROMO
CHROMED BRASS

Flussometro temporizzato esterno da 1". Pressione ottimale da 0,5 a 3 atm. Tempo apertura 3/5"

1" brass external flush valve flowmeter. Advisable pressure from 0,5 to 3 atm. Standard opening time 3/5"